

Transmittance **$U_w \geq 1.5$ (W/m²K)**

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	26 mm
Minimum glazing	6 mm
Maximum acoustic insulation	Rw = 39 dB

Sightlines

Frame	60, 65, 77, 80 mm
	106, 126 mm 3 rails
Sash	33 / 37 mm

Profile Thickness

Door	1.5 mm
------	--------

Polyamide strip length

14.6 - 20 mm

Maximum dimensions / Sash

Width (L) = 2,200 mm

Height (H) = 2,600 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash	100 kg 45° sash encounter
	200 kg 90° sash encounter

Categories achieved at test centre

Protection against atmospheric agents.

Air permeability**(UNE-EN 12207): Class 3****Water tightness****(UNE-EN 12208): Class 7A****Wind resistance****(UNE-EN 12210): Class C5**

* Reference test 1.20 x 1.20 m / 2 sashes.

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy**

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Sliding with 2, 3, 4 & 6 sashes.

Possibility of 3 rails.

1 & 2 rails pocket sliding door of 1,2 & 4 sashes.

