

4600 PLUS LIFT & SLIDE TB



Transmittance

$U_w \geq 0.65$ (W/m²K)

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing **65 mm**

Minimum glazing **22 mm**

Sightlines

Frame 180 mm, 280 mm 3 rails,
380 mm 4 rails

Sash 80 mm

Maximum dimensions / Sash

Width (L) = 3,300 mm

Height (H) = 3,300 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 400 kg

Categories achieved at test centre

Protection against atmospheric agents.

Air permeability

(UNE-EN 12207): Class 4

Water tightness

(UNE-EN 12208): Class E750*

Wind resistance

(UNE-EN 12210): Class C5**

* Reference test 4.0 x 2.5 m / 1 sash + 1 fixed light

**Reference test 4.0 x 2.5 m / 2 sashes

Test verified by

ALUMINIOS CORTIZO S.A.U.

Extrusion alloy

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Sliding

1 rail (1 sash + 1 fixed light), 2, 3 & 4 rails

Possibility of 90° opening without mullion

