

6200 SLIDING

Transmittance

$U_w \geq 3.2$ (W/m²K)

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing **15 mm**

Minimum glazing **4 mm**

Maximum acoustic insulation **R_w = 35 dB**

Sightlines

Frame 60 mm

Sash 22 mm

Profile Thickness

Window 1.25 mm

Maximum dimensions / Sash

Width (L) = 800 mm

Height (H) = 2,100 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 80 kg

Categories achieved at test centre

Protection against atmospheric agents.

Air permeability

(UNE-EN 12207): Class 3

Water tightness

(UNE-EN 12208): Class 7A

Wind resistance

(UNE-EN 12210): Class C3

* Reference test 1.12 x 1.15 m / 2 sashes

Test verified by

ALUMINIOS CORTIZO S.A.U.

Extrusion alloy

6063 T-5

Finishes

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewma Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Sliding with 2, 3, 4 & 6 sashes.

Possibility of 3 rails.

Possibility of double window.

