

# COR 60 HIDDEN SASH TB

## Transmittance

**$U_w \geq 1.5$  (W/m<sup>2</sup>K)**

Consult typology, dimensions and glass.

## Acoustic insulation

Maximum glazing	<b>34 mm</b>
Minimum glazing	<b>16 mm</b>
Maximum acoustic insulation	<b>Rw = 45 dB</b>

## Sightlines

Frame	60 mm
Sash	60 mm

## Profile Thickness

Window	1.6 mm
Balcony door	1.6 mm

**Polyamide strip length** 24 mm

## Maximum dimensions / Sash

Width (L) = 1,300 mm

Height (H) = 2,400 mm

Consult maximum weight and dimensions according to typologies.

**Maximum weight / Sash** 160 kg

## Categories achieved at test centre

Protection against atmospheric agents.

### Air permeability

**(UNE-EN 12207): Class 4**

### Water tightness

**(UNE-EN 12208): Class 9A**

### Wind resistance

**(UNE-EN 12210): Class C5**

\* Reference test 1.13 x 1.16 m / 1 sash.

Test verified by

**ALUMINIOS CORTIZO S.A.U.**

**Extrusion alloy** 6063 T-5

## Finishes

Possibility of dual colour

Colour powder coating (RAL, mottled & rough)

According to Qualicoat >60 microns

Wood effect powder coating

According to Qualideco standard

Anodised

According to Ewva Euras / Standard Class 15 / Optionally Class 20 and 25

## Opening possibilities

Inward opening: 1 & 2 sash side hung, 1 & 2 sash tilt & turn and bottom hung.

