

COR 70 HIDDEN SASH C16 ST TB

**Transmittance** **$U_w \geq 1.0$ (W/m²K)**

Consult typology, dimensions and glass.

Acoustic insulationFixed light maximum glazing **40 mm**Window maximum glazing **38 mm**Maximum acoustic insulation **Rw = 45 dB****Sightlines**

Frame 70 mm

Sash 70 mm

Profile Thickness

Window 1.6 mm

Polyamide strip length 35 mm**Maximum dimensions / Sash**

Width (L) = 1,300 mm

Height (H) = 2,400 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 150 kg**Certificates**

DTA certification from CSTB lab.

**Categories achieved at test centre**

Protection against atmospheric agents.

Air permeability**(UNE-EN 12207): Class 4****Water tightness****(UNE-EN 12208): Class E1200****Wind resistance****(UNE-EN 12210): Class C5**

* Reference test 1.23 x 1.48 m / 2 sashes.

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy**

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Inward opening: side hung, tilt & turn and bottom hung.

