

Transmittance **$U_w \geq 0.9$ (W/m²K)**

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	56 mm
Minimum glazing	36 mm
Maximum acoustic insulation	Rw = 43 dB

Sightlines

Frame	180 mm 278 mm 3 rails
Sash	69 mm

Profile Thickness

Door	2.0 mm
------	--------

Polyamide strip length

Frame	40 mm
Sash	18 / 32 mm

Maximum dimensions / Sash

Width (L) = 4,000 mm

Height (H) = 4,000 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash

400 kg Manual
700 kg Motorised

Categories achieved at test centre

Protection against atmospheric agents.

Air permeability**(UNE-EN 12207): Class 4****Water tightness****(UNE-EN 12208): Class 7A* / 9A******Wind resistance****(UNE-EN 12210): Class C3* / C4****

* Balcony door reference test 4,00 x 3,00 m / 2 sashes

** Balcony door reference test 4,00 x 3,00 m / 1 sash + 1 fixed light

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy**

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewva Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Sliding with 1, 2, 3, 4 & 6 sashes

Possibility of 1, 2, 3 or 4 rails

Possibility of corner opening sash at 90° without a mullion

Pocket sliding door of 1, 2, 3 & 4 sashes

