

**Transmittance** **$U_w \geq 1.3$  (W/m<sup>2</sup>K)**

Consult typology, dimensions and glass.

**Acoustic insulation**

Maximum glazing	<b>30 mm</b>
Minimum glazing	<b>26 mm</b>
Maximum acoustic insulation	<b>Rw = 41 dB</b>

**Sightlines**

Frame	116 mm
	182 mm 3 rails
Sash	37 mm

**Profile Thickness**

Door	1.7 mm
------	--------

**Polyamide strip length** 16 - 24 mm**Maximum dimensions / Sash**

Width (L) = 2,500 mm

Height (H) = 3,000 mm

Consult maximum weight and dimensions according to typologies.

**Maximum weight / Sash** 320 kg**Categories achieved at test centre**

Protection against atmospheric agents.

**Air permeability****(UNE-EN 12207): Class 4****Water tightness****(UNE-EN 12208): Class 7A****Wind resistance****(UNE-EN 12210): Class C5**

\* Reference test 1.23 x 1.55 m / 1 sash + 1 fixed light

**Security test:** PAS24 ☒

Passed

Test verified by

**ALUMINIOS CORTIZO S.A.U.****Extrusion alloy**

6063 T-5

**Finishes**

Possibility of dual colour.

Colour powder coating (RAL, mottled &amp; rough).

According to Qualicoat &gt;60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

**Opening possibilities**

Sliding with 1, 2, 3, 4 &amp; 6 sashes

Possibility of 1, 2 or 3 rails

Possibility of inner and outer corner sash at 90° without a mullion

Pocket sliding door of 1, 2, 3, 4 &amp; 6 sashes

